

# InsurIQ API

DATABASE STORED PROCEDURE API'S  
CYBERCOM INTERNATIONAL

# Contents

Agency.....	2
STORED PROCEDURE: <b>pAPI_Agency_Select</b> .....	2
Broker.....	3
STORED PROCEDURE: <b>pAPI_Broker_Select</b> .....	3
STORED PROCEDURE: <b>pAPI_Broker_Create</b> .....	4
STORED PROCEDURE: <b>pAPI_Broker_Update</b> .....	7
BrokerStateLicense .....	10
STORED PROCEDURE: <b>pAPI_BrokerStateLicense_Create</b> .....	10
STORED PROCEDURE: <b>pAPI_BrokerStateLicense_Update</b> .....	12
Carrier .....	14
STORED PROCEDURE: <b>pAPI_Carrier_Select</b> .....	14
CarrierAppointment.....	15
STORED PROCEDURE: <b>pAPI_CarrierAppointment_Create</b> .....	15
STORED PROCEDURE: <b>pAPI_CarrierAppointment_Update</b> .....	17
STORED PROCEDURE: <b>pAPI_CarrierAppointment_Delete</b> .....	19
GroupAccountBroker .....	21
STORED PROCEDURE: <b>pAPI_GroupAccountBroker_Create</b> .....	21
STORED PROCEDURE: <b>pAPI_GroupAccountBroker_Update</b> .....	23
STORED PROCEDURE: <b>pAPI_GroupAccountBroker_Delete</b> .....	25

# Agency

## STORED PROCEDURE: pAPI\_Agency\_Select

### Purpose

Returns all agencies.

### Input Parameters

There are no input parameters.

### Output Parameters

There are no output parameters.

### Result Set

Result set with the following fields will be returned:

Column #	Column name	Column type	Example value
1	AgencyNumber	Varchar(31)	A1123
2	AgencyName	Varchar(100)	A.B. LYNCH INSUANCE INC

### Example:

```
EXECUTE pAPI_Agency_Select;
```

	AgencyNumber	AgencyName
1	A1123	A.B. LYNCH INSUANCE INC
2	A1118	ACCURATE INSURANCE SERVICES
3	A1115	ACHIEVE FINANCIAL INDEPENDENCE INC
4	A1122	Acme Agency
5	A1125	AON Call Center Test Agency

# Broker

## STORED PROCEDURE: **pAPI\_Broker\_Select**

### Purpose

Returns all brokers.

### Input Parameters

There are no input parameters.

### Output Parameters

There are no output parameters.

### Result Set

Result set with the following fields will be returned:

Column #	Column name	Column type	Example value
1	BrokerNumber	Varchar(31)	B1282
2	FirstName	Varchar(50)	Greg
3	LastName	Varchar(50)	Cheves
4	EmailAddress	Varchar(128)	gregcheves@cybercom-intl.com
5	ActiveFlag	Bit	1
6	AgencyNumber	Varchar(31)	A1106

### Example:

```
EXECUTE pAPI_Broker_Select;
```

	BrokerNumber	FirstName	LastName	EmailAddress	ActiveFlag	AgencyNumber
1	B1224	Teresa D	Abington	terie@baryinsurance.com	1	A1124
2	B1221	Frank H	Adams	frank.adams@afbic.com	1	A1124
3	B1144	B	Agent	bagent@agenttest.com	1	A1106
4	B1145	C	Agent	cagent@agenttest.com	1	A1106
5	B1146	D	Agent	Dagent@agenttest.com	1	A1106

## STORED PROCEDURE: pAPI\_Broker\_Create

### Purpose

Creates a new broker.

### Input Parameters

Parameter	Type	Nullable	Example value
@AgencyNumber	Varchar(31)	No	A1106
@FirstName	Varchar(50)	No	Greg
@LastName	Varchar(50)	No	Cheves
@EmailAddress	Varchar(128)	No	test@cybercom-intl.com
@Address1	Varchar(100)	Yes	1 North Test Way
@Address2	Varchar(100)	Yes	Apt 213
@City	Varchar(50)	Yes	Jacksonville
@StateAbbr	Varchar(2)	Yes	FL
@PostalCode	Varchar(50)	Yes	32208
@Phone	Varchar(30)	Yes	9041111111
@LoginUID	Varchar(50)	Yes	test@cybercom-intl.com
@LoginPWD	Varchar(100)	Yes	C1D62BCBA7618C6CBB10DC3E4AE381A5
@Fax	Varchar(30)	Yes	9042222222
@EIN	Varchar(100)	Yes	<null>
@SignedPCKDate	Datetime	Yes	2017-04-01
@AIGAppointmentDate	Datetime	Yes	2017-01-13
@ExternalBrokerNumber	Varchar(25)	Yes	BB1111
@AgencyBrokerType	Varchar(50)	Yes	Internal
@SSN	Varchar(200)	Yes	576FF4619DB2ADA8D095526C6BF0018465EFAEDB
@ManagerFlag	Bit	Yes	0
@AcclaimAccessFlag	Bit	Yes	0
@AcclaimSubmitFlag	Bit	Yes	0

### Output Parameters

Parameter	Type	Nullable	Example value
@SuccessFlag	Bit	Yes	1
@ResultsMessage	Varchar(max)	Yes	Success Creating Broker: Gregory Cheves with BrokerID = 1428
@BrokerNumber	Varchar(31)	Yes	B1428

### Result Set

There is no result set returned.

## Example successful call:

```
DECLARE @rSuccessFlag bit
DECLARE @rBrokerNumber varchar(31)
DECLARE @rResultsMessage varchar(max)

EXECUTE pAPI_Broker_Create
    @AgencyNumber = 'A1106',
    @FirstName = 'Greg',
    @LastName = 'Cheves',
    @EmailAddress = 'test@cybercom-intl.com',
    @Address1 = '1 North Test Way',
    @Address2 = 'Apt 213',
    @City = 'Jacksonville',
    @StateAbbr = 'FL',
    @Postalcode = '32208',
    @Phone = '9041111111',
    @LoginUID = 'test@cybercom-intl.com',
    @LoginPWD = 'C1D62BCBA7618C6CBB10DC3E4AE381A5',
    @Fax = '9042222222',
    @EIN = null,
    @SignedPCKDate = '2017-04-01',
    @AIGAppointmentDate = '2017-01-13',
    @ExternalBrokerNumber = 'BB1111',
    @AgencyBrokerType = 'Internal',
    @SSN = '576FF4619DB2ADA8D095526C6BF0018465EFAEDA',
    @SuccessFlag = @rSuccessFlag output,
    @BrokerNumber = @rBrokerNumber output,
    @ResultsMessage = @rResultsMessage output;

SELECT
    @rSuccessFlag as SuccessFlag,
    @rResultsMessage as ResultsMessage,
    @rBrokerNumber as BrokerNumber;
```

	SuccessFlag	ResultsMessage	BrokerNumber
1	1	Success Creating Broker: Greg Cheves with BrokerID = 1436	B1436

## Example failed call:

```
DECLARE @rSuccessFlag bit
DECLARE @rBrokerNumber varchar(31)
DECLARE @rResultsMessage varchar(max)

EXECUTE pAPI_Broker_Create
    @AgencyNumber = 'A1106',
    @FirstName = 'Greg',
    @LastName = 'Cheves',
    @EmailAddress = 'test@cybercom-intl.com',
    @Address1 = '1 North Test Way',
    @Address2 = 'Apt 213',
    @City = 'Jacksonville',
    @StateAbbr = 'FA',
    @Postalcode = '32208',
    @Phone = '9041111111',
    @LoginUID = 'test@cybercom-intl.com',
    @LoginPWD = 'C1D62BCBA7618C6CBB10DC3E4AE381A5',
    @Fax = '9042222222',
    @EIN = null,
    @SignedPCKDate = '2017-04-01',
    @AIGAppointmentDate = '2017-01-13',
    @ExternalBrokerNumber = 'BB1111',
    @AgencyBrokerType = 'Internal',
    @SSN = '576FF4619DB2ADA8D095526C6BF0018465EFAEDA',
    @SuccessFlag = @rSuccessFlag output,
    @BrokerNumber = @rBrokerNumber output,
    @ResultsMessage = @rResultsMessage output;

SELECT
    @rSuccessFlag as SuccessFlag,
    @rResultsMessage as ResultsMessage,
    @rBrokerNumber as BrokerNumber;
```

	SuccessFlag	ResultsMessage	BrokerNumber
1	0	Error Creating Broker: StateAbbr=[FA] is not a valid state.	NULL

## STORED PROCEDURE: pAPI\_Broker\_Update

### Purpose

Updates an existing broker.

### Input Parameters

Parameter	Type	Nullable	Example value
@BrokerNumber	Varchar(31)	No	B1436
@AgencyNumber	Varchar(31)	No	A1106
@FirstName	Varchar(50)	No	Greg
@LastName	Varchar(50)	No	Cheves
@EmailAddress	Varchar(128)	No	test@cybercom-intl.com
@Address1	Varchar(100)	Yes	1 North Test Way
@Address2	Varchar(100)	Yes	Apt 213
@City	Varchar(50)	Yes	Jacksonville
@StateAbbr	Varchar(2)	Yes	FL
@PostalCode	Varchar(50)	Yes	32208
@Phone	Varchar(30)	Yes	9041111111
@LoginUID	Varchar(50)	Yes	test@cybercom-intl.com
@LoginPWD	Varchar(100)	Yes	C1D62BCBA7618C6CBB10DC3E4AE381A5
@Fax	Varchar(30)	Yes	9042222222
@EIN	Varchar(100)	Yes	99-2323421
@SignedPCKDate	Datetime	Yes	2017-04-01
@AIGAppointmentDate	Datetime	Yes	2017-03-13
@ExternalBrokerNumber	Varchar(25)	Yes	BB1111
@AgencyBrokerType	Varchar(50)	Yes	Internal
@SSN	Varchar(200)	Yes	576FF4619DB2ADA8D095526C6BF0018465EFAEDB
@ManagerFlag	Bit	Yes	0
@AcclaimAccessFlag	Bit	Yes	0
@AcclaimSubmitFlag	Bit	Yes	0

### Output Parameters

Parameter	Type	Nullable	Example value
@SuccessFlag	Bit	Yes	1
@ResultsMessage	Varchar(max)	Yes	Success Updating Broker: Gregory Cheves with BrokerID = 1428

### Result Set

There is no result set returned.



## Example successful call:

```
DECLARE @rSuccessFlag bit
DECLARE @rResultsMessage varchar(max)

EXECUTE pAPI_Broker_Update
    @BrokerNumber = 'B1436',
    @AgencyNumber = 'A1106',
    @FirstName = 'Greg',
    @LastName = 'Cheves',
    @EmailAddress = 'test@cybercom-intl.com',
    @Address1 = '1 North Test Way',
    @Address2 = 'Apt 213',
    @City = 'Jacksonville',
    @StateAbbr = 'FL',
    @Postalcode = '32208',
    @Phone = '9041111111',
    @LoginUID = 'test@cybercom-intl.com',
    @LoginPWD = 'C1D62BCBA7618C6CBB10DC3E4AE381A5',
    @Fax = '9042222222',
    @EIN = null,
    @SignedPCKDate = '2017-04-01',
    @AIGAppointmentDate = '2017-01-13',
    @ExternalBrokerNumber = 'BB1111',
    @AgencyBrokerType = 'Internal',
    @SSN = '576FF4619DB2ADA8D095526C6BF0018465EFAEDA',
    @ActiveFlag = 1,
    @SuccessFlag = @rSuccessFlag output,
    @ResultsMessage = @rResultsMessage output;

SELECT
    @rSuccessFlag as SuccessFlag,
    @rResultsMessage as ResultsMessage;
```

	SuccessFlag	ResultsMessage	BrokerNumber
1	1	Success Updating Broker: Greg Cheves with BrokerID = 1436	B1436

## Example failed call:

```
DECLARE @rSuccessFlag bit
DECLARE @rResultsMessage varchar(max)

EXECUTE pAPI_Broker_Update
    @BrokerNumber = 'B1437',
    @AgencyNumber = 'A1106',
    @FirstName = 'Greg',
    @LastName = 'Cheves',
    @EmailAddress = 'test@cybercom-intl.com',
    @Address1 = '1 North Test Way',
    @Address2 = 'Apt 213',
    @City = 'Jacksonville',
    @StateAbbr = 'FA',
    @Postalcode = '32208',
    @Phone = '9041111111',
    @LoginUID = 'test@cybercom-intl.com',
    @LoginPWD = 'C1D62BCBA7618C6CBB10DC3E4AE381A5',
    @Fax = '9042222222',
    @EIN = null,
    @SignedPCKDate = '2017-04-01',
    @AIGAppointmentDate = '2017-01-13',
    @ExternalBrokerNumber = 'BB1111',
    @AgencyBrokerType = 'Internal',
    @SSN = '576FF4619DB2ADA8D095526C6BF0018465EFAEDA',
    @ActiveFlag = 1,
    @SuccessFlag = @rSuccessFlag output,
    @ResultsMessage = @rResultsMessage output;

SELECT
    @rSuccessFlag as SuccessFlag,
    @rResultsMessage as ResultsMessage;
```

	SuccessFlag	ResultsMessage	BrokerNumber
1	0	Error Updating Broker: StateAbbr=[FA] is not a valid state.	B1437

# BrokerStateLicense

STORED PROCEDURE: **pAPI\_BrokerStateLicense\_Create**

## Purpose

Creates a new state license entry for a broker.

## Input Parameters

Parameter	Type	Nullable	Example value
@BrokerNumber	Varchar(31)	No	B1426
@StateAbbr	Varchar(2)	No	FL
@LicenseNumber	Varchar(50)	Yes	289394
@EffectiveDate	Datetime	Yes	2017-01-01
@ExpirationDate	Datetime	Yes	<null>
@LicenseStateScope	Varchar(30)	Yes	State Of Residence
@LicenseType	Varchar(30)	Yes	A&H

## Output Parameters

Parameter	Type	Nullable	Example value
@SuccessFlag	Bit	Yes	1
@ResultsMessage	Varchar(max)	Yes	Success Creating Broker State License: Greg Cheves for FL.

## Result Set

There is no result set returned.

## Example successful call:

```
DECLARE @rSuccessFlag bit
DECLARE @rResultsMessage varchar(max)

EXECUTE pAPI_BrokerStateLicense_Create
    @BrokerNumber = 'B1444',
    @StateAbbr = 'FL',
    @LicenseNumber = '289394',
    @EffectiveDate = '2017-01-01',
    @ExpirationDate = NULL,
    @LicenseStateScope = 'State Of Residence',
    @LicenseType = 'A&H',
    @SuccessFlag = @rSuccessFlag output,
    @ResultsMessage = @rResultsMessage output

SELECT
    @rSuccessFlag as SuccessFlag,
    @rResultsMessage as ResultsMessage;
```

	SuccessFlag	ResultsMessage
1	1	Success Creating Broker State License: Greg Cheves for FL.

## Example failed call:

```
DECLARE @rSuccessFlag bit
DECLARE @rResultsMessage varchar(max)

EXECUTE pAPI_BrokerStateLicense_Create
    @BrokerNumber = 'B1444',
    @StateAbbr = 'FA',
    @LicenseNumber = 'FL289394',
    @EffectiveDate = '2017-02-01',
    @ExpirationDate = NULL,
    @LicenseStateScope = 'State Of Residence',
    @LicenseType = 'A&H',
    @SuccessFlag = @rSuccessFlag output,
    @ResultsMessage = @rResultsMessage output

SELECT
    @rSuccessFlag as SuccessFlag,
    @rResultsMessage as ResultsMessage;
```

	SuccessFlag	ResultsMessage
1	0	Error Creating Broker State License: StateAbbr=[FA] is not a valid state.

## STORED PROCEDURE: **pAPI\_BrokerStateLicense\_Update**

### Purpose

Updates an existing state license entry for a broker.

### Input Parameters

Parameter	Type	Nullable	Example value
@BrokerNumber	Varchar(31)	No	B1426
@StateAbbr	Varchar(2)	No	FL
@LicenseNumber	Varchar(50)	Yes	289394
@EffectiveDate	Datetime	Yes	2017-01-01
@ExpirationDate	Datetime	Yes	<null>
@LicenseStateScope	Varchar(30)	Yes	
@LicenseType	Varchar(30)	Yes	

### Output Parameters

Parameter	Type	Nullable	Example value
@SuccessFlag	Bit	Yes	1
@ResultsMessage	Varchar(max)	Yes	Success Updating Broker State License: Greg Cheves for FL.

### Result Set

There is no result set returned.

## Example successful call:

```
DECLARE @rSuccessFlag bit
DECLARE @rResultsMessage varchar(max)

EXECUTE pAPI_BrokerStateLicense_Update
    @BrokerNumber = 'B1444',
    @StateAbbr = 'FL',
    @LicenseNumber = 'FL289394',
    @EffectiveDate = '2017-01-01',
    @ExpirationDate = NULL,
    @LicenseStateScope = 'State Of Residence',
    @LicenseType = 'A&H',
    @SuccessFlag = @rSuccessFlag output,
    @ResultsMessage = @rResultsMessage output

SELECT
    @rSuccessFlag as SuccessFlag,
    @rResultsMessage as ResultsMessage;
```

	SuccessFlag	ResultsMessage
1	1	Success Updating Broker State License: Greg Cheves for FL.

## Example failed call:

```
DECLARE @rSuccessFlag bit
DECLARE @rResultsMessage varchar(max)

EXECUTE pAPI_BrokerStateLicense_Update
    @BrokerNumber = 'B1444',
    @StateAbbr = 'FA',
    @LicenseNumber = '289394',
    @EffectiveDate = '2017-02-01',
    @ExpirationDate = NULL,
    @LicenseStateScope = 'State Of Residence',
    @LicenseType = 'A&H',
    @SuccessFlag = @rSuccessFlag output,
    @ResultsMessage = @rResultsMessage output

SELECT
    @rSuccessFlag as SuccessFlag,
    @rResultsMessage as ResultsMessage;
```

	SuccessFlag	ResultsMessage
1	0	Error Updating Broker State License: Broker with BrokerNumber=[B1448] does not have license for FA., StateAbbr=[FA] is not a valid state.

# Carrier

## STORED PROCEDURE: **pAPI\_Carrier\_Select**

### Purpose

Returns all carriers.

### Input Parameters

There are no input parameters.

### Output Parameters

There are no output parameters.

### Result Set

Result set with the following fields will be returned:

Column #	Column name	Column type	Example value
1	CarrierName	Varchar(100)	ARAG Insurance Company
2	ActiveFlag	Bit	1

### Example:

```
EXECUTE pAPI_Carrier_Select;
```

	CarrierName	ActiveFlag
1	_Placeholder Carrier	1
2	American National	1
3	ARAG Insurance Company	1
4	Assist America	1
5	Berkley Life and Health Insurance Company	1

# CarrierAppointment

## STORED PROCEDURE: pAPI\_CarrierAppointment\_Create

### Purpose

Creates a new state license entry for a broker.

### Input Parameters

Parameter	Type	Nullable	Example value
@BrokerNumber	Varchar(31)	No	B1426
@CarrierName	Varchar(100)	No	Securian
@AgencyNumber	Varchar(31)	No	A1106
@AppointedFlag	Bit	Yes	1
@CarrierAppointmentNumber	Varchar(25)	Yes	<null>

### Output Parameters

Parameter	Type	Nullable	Example value
@SuccessFlag	Bit	Yes	1
@ResultsMessage	Varchar(max)	Yes	Success Creating Carrier Appointment: Greg Cheves with BrokerID = 1426 for Carrier = Securian.

### Result Set

There is no result set returned.

### Example successful call:

```
DECLARE @rSuccessFlag bit
DECLARE @rResultsMessage varchar(max)

EXECUTE pAPI_CarrierAppointment_Create
    @BrokerNumber = 'B1450',
    @CarrierName = 'Securian',
    @AgencyNumber = 'A1106',
    @AppointedFlag = 1,
    @CarrierAppointmentNumber = 'C234234',
    @SuccessFlag = @rSuccessFlag output,
    @ResultsMessage = @rResultsMessage output

SELECT
    @rSuccessFlag as SuccessFlag,
    @rResultsMessage as ResultsMessage;
```

	SuccessFlag	ResultsMessage
1	1	Success Creating Carrier Appointment: Greg Cheves with BrokerID = 1450 for Carrier = Securian



## Example failed call:

```
DECLARE @rSuccessFlag bit
DECLARE @rResultsMessage varchar(max)

EXECUTE pAPI_CarrierAppointment_Create
    @BrokerNumber = 'B1450',
    @CarrierName = 'Securiannn',
    @AgencyNumber = 'A1106',
    @AppointedFlag = 1,
    @CarrierAppointmentNumber = 'C234234',
    @SuccessFlag = @rSuccessFlag output,
    @ResultsMessage = @rResultsMessage output

SELECT
    @rSuccessFlag as SuccessFlag,
    @rResultsMessage as ResultsMessage;
```

	SuccessFlag	ResultsMessage
1	0	Error Creating Carrier Appointment: CarrierName=[Securiannn] was not found in Carrier table.

## STORED PROCEDURE: pAPI\_CarrierAppointment\_Update

### Purpose

Updates an existing state license entry for a broker.

### Input Parameters

Parameter	Type	Nullable	Example value
@BrokerNumber	Varchar(31)	No	B1426
@CarrierName	Varchar(100)	No	Securian
@AgencyNumber	Varchar(31)	No	A1106
@AppointedFlag	Bit	Yes	1
@CarrierAppointmentNumber	Varchar(25)	Yes	<null>

### Output Parameters

Parameter	Type	Nullable	Example value
@SuccessFlag	Bit	Yes	1
@ResultsMessage	Varchar(max)	Yes	Success Updating Carrier Appointment: Greg Cheves with BrokerID = 1426 for Carrier = Securian.

### Result Set

There is no result set returned.

### Example successful call:

```
DECLARE @rSuccessFlag bit
DECLARE @rResultsMessage varchar(max)

EXECUTE pAPI_CarrierAppointment_Update
    @BrokerNumber = 'B1450',
    @CarrierName = 'Securian',
    @AgencyNumber = 'A1106',
    @AppointedFlag = 1,
    @CarrierAppointmentNumber = 'C234234',
    @SuccessFlag = @rSuccessFlag output,
    @ResultsMessage = @rResultsMessage output

SELECT
    @rSuccessFlag as SuccessFlag,
    @rResultsMessage as ResultsMessage;
```

	SuccessFlag	ResultsMessage
1	1	Success Updating Carrier Appointment: Greg Cheves with BrokerID = 1450 for Carrier = Securian

## Example failed call:

```
DECLARE @rSuccessFlag bit
DECLARE @rResultsMessage varchar(max)

EXECUTE pAPI_CarrierAppointment_Update
    @BrokerNumber = 'B1450',
    @CarrierName = 'Securiannn',
    @AgencyNumber = 'A1106',
    @AppointedFlag = 1,
    @CarrierAppointmentNumber = 'C234234',
    @SuccessFlag = @rSuccessFlag output,
    @ResultsMessage = @rResultsMessage output

SELECT
    @rSuccessFlag as SuccessFlag,
    @rResultsMessage as ResultsMessage;
```

	SuccessFlag	ResultsMessage
1	0	Error Updating Carrier Appointment: CarrierName=[Securiannn] was not found in Carrier table.

## STORED PROCEDURE: pAPI\_CarrierAppointment\_Delete

### Purpose

Deletes an existing state license entry for a broker.

### Input Parameters

Parameter	Type	Nullable	Example value
@BrokerNumber	Varchar(31)	No	B1426
@CarrierName	Varchar(100)	No	Securian
@AgencyNumber	Varchar(31)	No	A1106

### Output Parameters

Parameter	Type	Nullable	Example value
@SuccessFlag	Bit	Yes	1
@ResultsMessage	Varchar(max)	Yes	Success Deleting Carrier Appointment: Greg Cheves with BrokerID = 1426 for Carrier = Securian.

### Result Set

There is no result set returned.

### Example successful call:

```
DECLARE @rSuccessFlag bit
DECLARE @rResultsMessage varchar(max)

EXECUTE pAPI_CarrierAppointment_Delete
    @BrokerNumber = 'B1450',
    @CarrierName = 'Securian',
    @AgencyNumber = 'A1106',
    @SuccessFlag = @rSuccessFlag output,
    @ResultsMessage = @rResultsMessage output

SELECT
    @rSuccessFlag as SuccessFlag,
    @rResultsMessage as ResultsMessage;
```

	SuccessFlag	ResultsMessage
1	1	Success Deleting Carrier Appointment: Greg Cheves with BrokerID = 1451 for Carrier = Securian

## Example failed call:

```
DECLARE @rSuccessFlag bit
DECLARE @rResultsMessage varchar(max)

EXECUTE pAPI_CarrierAppointment_Delete
    @BrokerNumber = 'B1450',
    @CarrierName = 'Securiannn',
    @AgencyNumber = 'A1106',
    @SuccessFlag = @rSuccessFlag output,
    @ResultsMessage = @rResultsMessage output

SELECT
    @rSuccessFlag as SuccessFlag,
    @rResultsMessage as ResultsMessage;
```

	SuccessFlag	ResultsMessage
1	0	Error Deleting Carrier Appointment: CarrierName=[Securiannn] was not found in Carrier table.

# GroupAccountBroker

## STORED PROCEDURE: pAPI\_GroupAccountBroker\_Create

### Purpose

Creates a new group account broker assignment.

### Input Parameters

Parameter	Type	Nullable	Example value
@BrokerNumber	Varchar(31)	No	B1426
@GroupNumber	Bigint	No	8859741
@GeneralAgencyCommission	Decimal(18,5)	Yes	2.01
@AgencyCommission	Decimal(18,5)	Yes	1.00
@BrokerCommission	Decimal(18,5)	Yes	1.00

### Output Parameters

Parameter	Type	Nullable	Example value
@SuccessFlag	Bit	Yes	1
@ResultsMessage	Varchar(max)	Yes	Success Creating Group Account Broker: Greg Cheves for IIQ Ecom demo.

### Result Set

There is no result set returned.

### Example successful call:

```
DECLARE @rSuccessFlag bit
DECLARE @rResultsMessage varchar(max)

EXECUTE pAPI_GroupAccountBroker_Create
    @BrokerNumber = 'B1450',
    @GroupNumber = 8859741,
    @GeneralAgencyCommission = 2.01,
    @AgencyCommission = 1.00,
    @BrokerCommission = 1.00,
    @SuccessFlag = @rSuccessFlag output,
    @ResultsMessage = @rResultsMessage output

SELECT
    @rSuccessFlag as SuccessFlag,
    @rResultsMessage as ResultsMessage;
```

	SuccessFlag	ResultsMessage
1	1	Success Creating Group Account Broker: Greg Cheves for IIQ Ecom demo.

## Example failed call:

```
DECLARE @rSuccessFlag bit
DECLARE @rResultsMessage varchar(max)

EXECUTE pAPI_GroupAccountBroker_Create
    @BrokerNumber = 'B1450',
    @GroupNumber = 88597414,
    @GeneralAgencyCommission = 2.01,
    @AgencyCommission = 1.00,
    @BrokerCommission = 1.00,
    @SuccessFlag = @rSuccessFlag output,
    @ResultsMessage = @rResultsMessage output

SELECT
    @rSuccessFlag as SuccessFlag,
    @rResultsMessage as ResultsMessage;
```

	SuccessFlag	ResultsMessage
1	0	Error Creating Group Account Broker: GroupAccount with GroupNumber=[88597413] does not exist.

## STORED PROCEDURE: pAPI\_GroupAccountBroker\_Update

### Purpose

Updates an existing group account broker assignment.

### Input Parameters

Parameter	Type	Nullable	Example value
@BrokerNumber	Varchar(31)	No	B1426
@GroupNumber	Bigint	No	8859741
@GeneralAgencyCommission	Decimal(18,5)	Yes	2.01
@AgencyCommission	Decimal(18,5)	Yes	1.00
@BrokerCommission	Decimal(18,5)	Yes	1.00

### Output Parameters

Parameter	Type	Nullable	Example value
@SuccessFlag	Bit	Yes	1
@ResultsMessage	Varchar(max)	Yes	Success Updating Group Account Broker: Greg Cheves for IIQ Ecom demo.

### Result Set

There is no result set returned.

### Example successful call:

```
DECLARE @rSuccessFlag bit
DECLARE @rResultsMessage varchar(max)

EXECUTE pAPI_GroupAccountBroker_Update
    @BrokerNumber = 'B1450',
    @GroupNumber = 8859741,
    @GeneralAgencyCommission = 3.23,
    @AgencyCommission = 0,
    @BrokerCommission = 0,
    @SuccessFlag = @rSuccessFlag output,
    @ResultsMessage = @rResultsMessage output

SELECT
    @rSuccessFlag as SuccessFlag,
    @rResultsMessage as ResultsMessage;
```

	SuccessFlag	ResultsMessage
1	1	Success Updating Group Account Broker: Greg Cheves for IIQ Ecom demo.



## Example failed call:

```
DECLARE @rSuccessFlag bit
DECLARE @rResultsMessage varchar(max)

EXECUTE pAPI_GroupAccountBroker_Update
    @BrokerNumber = 'B1450',
    @GroupNumber = 885974134,
    @GeneralAgencyCommission = 3.23,
    @AgencyCommission = 0,
    @BrokerCommission = 0,
    @SuccessFlag = @rSuccessFlag output,
    @ResultsMessage = @rResultsMessage output

SELECT
    @rSuccessFlag as SuccessFlag,
    @rResultsMessage as ResultsMessage;
```

	SuccessFlag	ResultsMessage
1	0	Error Updating Group Account Broker: GroupAccount with GroupNumber=[885974134] does not exist.

## STORED PROCEDURE: pAPI\_GroupAccountBroker\_Delete

### Purpose

Deletes an existing group account broker assignment.

### Input Parameters

Parameter	Type	Nullable	Example value
@BrokerNumber	Varchar(31)	No	B1426
@GroupNumber	Bigint	No	8859741

### Output Parameters

Parameter	Type	Nullable	Example value
@SuccessFlag	Bit	Yes	1
@ResultsMessage	Varchar(max)	Yes	Success Deleting Group Account Broker: Greg Cheves for IIQ Ecom demo.

### Result Set

There is no result set returned.

### Example successful call:

```
DECLARE @rSuccessFlag bit
DECLARE @rResultsMessage varchar(max)

EXECUTE pAPI_GroupAccountBroker_Delete
    @BrokerNumber = 'B1450',
    @GroupNumber = 8859741,
    @SuccessFlag = @rSuccessFlag output,
    @ResultsMessage = @rResultsMessage output

SELECT
    @rSuccessFlag as SuccessFlag,
    @rResultsMessage as ResultsMessage;
```

	SuccessFlag	ResultsMessage
1	1	Success Deleting Group Account Broker: Greg Cheves for IIQ Ecom demo.

## Example failed call:

```
DECLARE @rSuccessFlag bit
DECLARE @rResultsMessage varchar(max)

EXECUTE pAPI_GroupAccountBroker_Delete
    @BrokerNumber = 'B1450',
    @GroupNumber = 885974142,
    @SuccessFlag = @rSuccessFlag output,
    @ResultsMessage = @rResultsMessage output

SELECT
    @rSuccessFlag as SuccessFlag,
    @rResultsMessage as ResultsMessage;
```

	SuccessFlag	ResultsMessage
1	0	Error Deleting Group Account Broker: GroupAccount with GroupNumber=[8859741343] does not exist.